



Audio Note

**ONGAKU**  
**kensei**

STEREO POWER  
AMPLIFIER

**OWNER'S INFORMATION**



## **CONTENTS**

- 1) IMPORTANT SAFETY INFORMATION**
- 2) CE DECLARATION OF CONFORMITY  
DISPOSAL  
POWER REQUIREMENTS**
- 3) INTRODUCTION**
- 4) OVERVIEW**
- 5) UNPACKING AND INSTALLATION**
- 6) VALVE INSTALLATION**
- 9) CONNECTION**
- 10) OPERATION**
- 11) TECHNICAL SPECIFICATIONS**
- 12) WARRANTY**
- 13) CONTACT INFORMATION**

# ! IMPORTANT SAFETY INFORMATION !



## **RISK OF SHOCK OR ELECTROCUTION! INTERNAL OPERATING VOLTAGES ARE LETHAL!**


Do not remove top cover, unless specifically instructed to do so in the user manual.

This unit contains fuses and other safety components in accordance with BS60065 requirements.

In the event of failure, replacement fuse or safety component must be of the same part type and value.

## **S UCH REPLACEMENT MUST ONLY BE CARRIED OUT BY A QUALIFIED SERVICE TECHNICIAN.**

Do not attempt to replace any fuses without first disconnecting the unit from the mains electricity supply.



This product must be earthed – ensure that the mains supply cable earth / ground is correctly connected.



This product generates high levels of heat. Adequate ventilation must be provided. Do not restrict airflow through any ventilation slots or place the unit on any surface that may restrict airflow.

Valve equipment operates at extremely high temperatures;  
**KEEP OUT OF THE REACH OF CHILDREN AND ANIMALS.**



Do not store or operate this unit in areas of high humidity or in close proximity to water / moisture.

Do not expose or immerse the unit in liquid of any kind.

## **OTHER SAFETY PRECAUTIONS: -**

Never touch the power cord with wet hands.

Always remove the power cord by grasping the plug, not the cable.

Never expose the unit to excessive heat or magnetism.

Never let an inexperienced person repair or reassemble the unit.

Never put anything, especially metal objects, inside the unit.

Never place excessive weight on the unit.

# CE DECLARATION OF CONFORMITY



We declare under our sole responsibility that this product is in conformity with the following standards or standardized documents:

BS EN 60065 in accordance with the regulations 73/23/EEC, 89/336/EEC (from 1 January 1997)

CE 94

Peter Qvortrup,  
Director  
Audio Note (UK) Limited  
Viscount House  
Star Road, Star Trading Estate  
Partridge Green  
West Sussex  
RH13 8RA  
United Kingdom

Tel: +44 (0)1273 830 800

Fax: +44 (0)1273 731 498



## DISPOSAL

This product must not be disposed of as normal household waste. To prevent possible harm to the environment please separate the product from other waste to ensure that it can be recycled in an environmentally safe manner. Please contact your retailer or the appropriate local government office for collection facilities.

## POWER REQUIREMENTS

Power requirements for electrical equipment vary depending on your geographical location. Please ensure that your unit meets the power requirements in your area. The power requirement for your unit is marked on the serial number plate, located on the rear panel.

If you are in doubt, please contact your dealer before plugging the unit into the mains supply.

# INTRODUCTION

Thank you for purchasing this Audio Note (UK) product. With the correct care it should give you many years of pleasure and enjoyment.

Please take the time to read all of the information in this manual before connecting your new component to an electrical supply or your system, to ensure both your safety and satisfaction.

Please note that due to our desire to continually improve products, specifications are subject to change without notice. Therefore it is important to refer to the manual that is supplied with your product for the most accurate information; manuals downloaded from our website or obtained from other sources may no longer fully apply to your product.

If you have any questions regarding the information contained within this document or your new component, please feel free to contact us: -

Audio Note (UK) Limited  
Viscount House  
Star Road, Star Trading Estate  
Partridge Green  
West Sussex  
RH13 8RA  
United Kingdom

Tel: +44 (0)1273 830 800  
Fax: +44 (0)1273 731 498  
e-mail: [info@audionote.co.uk](mailto:info@audionote.co.uk)



## ONGAKU KENSEI

Congratulations on your purchase of the Audio Note (UK) ONGAKU Kensei stereo power amplifier.

The ONGAKU integrated has rightly earned a place in history; its name is synonymous with the finest possible audio reproduction, and for once the reality is equal to the legend! The ONGAKU Kensei shares the same circuit as its integrated sibling, but instead is equipped with a single pair of Balanced / XLR inputs. Each input is connected to an in-house custom designed and manufactured, fully silver wired, balanced input transformer, offering the perfect input interface for any of our Balanced output equipped preamplifiers.

It is a Pure Class A Singled Ended valve amplifier that uses the highly regarded VT-4C / 211 triode valve, producing a level of performance that is radically superior to any other current designs.

Only the finest possible components have been employed: -

Audio Note (UK) Silver wire has been use exclusively for all internal wiring, including all transformers and power supply connections.

Audio Note 2 watt Tantalum resistors have been used throughout.

All capacitors are either Black Gate Electrolytic or Audio Note (UK) silver foil.

All transformers are our own in-house custom designed and manufactured devices; driver and output transformers are fully silver wired AN-Perma 50 nickel C-core and the mains transformer is a fully silver wired HiB double C core.

No stereo power amplifier has ever produced the levels of musical purity delivered by the ONGAKU Kensei... It is without doubt the finest possible stereo chassis power amplifier available today.

It has been specifically engineered for sonic performance rather than technical specification, and fulfills all Audio Note (UK) Level 5 criteria: -

- Pure Class A operation
- Zero Negative Feedback
- Single Ended Output Stage
- Valve Rectification
- Directly Heated Triode operation
- Materials and component quality

## UNPACKING AND INSTALLATION

Please take care when unpacking your ONGAKU Kensei stereo power amplifier. Choose a clean, clear location to unpack your unit. Be aware that the amplifier is very heavy; before attempting to unpack or lift the unit, check the weight and if necessary use more than one person so that it can be moved safely and easily.

We recommend that you retain and carefully store all of the original packing materials, in case transportation / shipping is required at a later date.

Select a suitable location for the unit. This should be a dry, dust free and level area, preferably shielded from direct sunlight and free from vibration. Also ensure that the location is stable and capable of carrying the weight of the unit.

A suitable mains power outlet must be close to the location; power cords must not be pulled or stretched tightly in an attempt to reach a wall socket. If the power cord will not easily reach the socket, choose a closer location!

Please ensure that adequate ventilation for the unit is provided, and that airflow through any ventilation slots in the unit is not restricted. We recommend a distance of at least 50cm free space is maintained above the unit, and preferably it should be sited in free space or on the top shelf of your equipment rack or table. Please also remember that valve equipment operates at extremely high temperatures, so a position that is inaccessible to any children or animals is essential.

## VALVE INSTALLATION

The amplifier is shipped without the valves installed. It is necessary to install the valves before the amplifier can be operated.

It is essential that the valves are installed correctly or ***serious damage that is not covered by the warranty will result.*** We recommend that your dealer perform this procedure for you if you are in any way unsure.

FIRSTLY, ENSURE THAT THE AMPLIFIER IS **NOT** CONNECTED TO A MAINS ELECTRICAL SUPPLY, AND THAT THE POWER CORD IS **NOT** CONNECTED TO THE AMPLIFIER.

Now remove the 6 valves that are packed inside the amplifier. Also inspect the amplifier to check that nothing has become damaged during transit.

Carefully unwrap the 6 valves. You will find the following: -

- 2 x 6V6 signal valves
- 2 x VT-4C output valves
- 2 x 5R4WGB rectifier valves

**Once again, please understand that it is absolutely vital these valves are fitted correctly.**

Looking from the front of the amplifier install the **VT-4C** valves first: -






## VALVE INSTALLATION continued...



Inspect a VT-4C valve and you will notice that there is a **small 'pin'** protruding from one side of the valve base; this locating pin ensures that the valve can only be correctly inserted into the amplifier in one way.



Also examine the **two large apertures** in the top plate of the amplifier, located between the two small valve sockets at the front of the amplifier and the black rectangular transformer covers. These are the insertion points for the VT-4C valves.

- 1) Gently hold a VT-4C valve, and locate the small side mounted pin on the valve base.
- 2) Line up this pin with the locating hole in the mounting aperture on the amplifier's top plate.
- 3) Gently insert the valve, and GENTLY twist in a clockwise direction, until the valve 'locks' in position, and no more movement can take place.

**Please make sure that steps (1), (2) and (3) are correct. Check again that both valves are fully inserted correctly in to their respective valve sockets.**

## VALVE INSTALLATION continued...



Looking from the back of the amplifier, insert the **5R4WGB** valves into the two empty sockets located on the left, situated between the black rectangular transformer covers and the loudspeaker connection binding posts. Locate the rib on the central pin of the valve and align with the valve base (it can only be inserted one way due to this locating rib) and with gentle but firm pressure insert the valve.



Finally, insert the **two 6V6 signal valves** into the front two sockets. The valves are identical and can only be inserted one way.

**Check one more time that all of the 6 valves are correctly fitted!**

## CONNECTION

**Line inputs** Being a stereo power amplifier, the ONGAKU Kensei is fitted with a pair of XLR / Balanced input sockets. Looking from the front of the amplifier, they are located towards the front of the left hand side panel. Connect the outputs from your preamplifier to these inputs.

**Ground Post** A ground post is provided for connection to those source components that also use a separate ground terminal.

**Speakers** Each channel is equipped with 2 colour coded binding posts for connection to your speakers. Looking from the front of the amplifier, the 2 binding posts to the left are for the left channel and the 2 binding posts to the right are for the right channel.

Connect the amplifiers black speaker output binding post to the black / negative terminal (also marked “ - ”) on the speaker.


Connect the amplifiers red speaker output binding post to the red / positive terminal (also marked “ + ”) on the speaker.

**Mains** The ONGAKU Kensei uses an IEC 320 mains inlet socket. Use the supplied mains cable to connect the unit to the local mains supply. The mains fuse and a spare are located in the inlet socket fuse drawer.


*Special Note – Make sure that all connections are tight and clean. For best results use good quality audio interconnects. Although it is perfectly acceptable to use cables manufactured by other companies, for best results and performance, we recommend our own Audio Note (UK) range of interconnects and loudspeaker cables. For further information, please consult your nearest Audio Note (UK) dealer, or alternatively please feel free to contact us directly.*

# CONNECTION continued...


## CABLE CONFIGURATION OPTIONS



CONVENTIONAL: SCREEN CONNECTED AT BOTH ENDS



SCREEN CONNECTED AT PREAMP END ONLY, TO ELIMINATE GROUND LOOPS



CABLE CONFIGURATION FOR RCA SINGLE ENDED PREAMP OUTPUT TO XLR BALANCED AMPLIFIER INPUT

# OPERATION

Once all the connections are completed and checked, ensure that the volume control of your preamplifier / source is at the minimum setting.

Turn on all components in the signal chain before the ONGAKU Kensei; the power amplifier should always be the LAST component to be switched ON, and the FIRST to be switched OFF.

Turn on the amplifier by using the rocker switch located at the top right of the rear panel, just above mains inlet socket (viewing the amplifier from the rear).

**Bedding in** The new amplifier requires about 200 hours of initial use (called “bedding in”) before the circuitry becomes stable and optimum performance is realized. As the amplifier “bed in” the sound will become increasingly smoother, detailed and open. Once the amplifiers have “bedded in” a warm up time of approximately 30 to 45 minutes is required each time the amplifiers are switched on before optimum sonic performance is reached.

**Cleaning** No special maintenance is required for the amplifier. Use a soft, clean lint free cloth to remove any surface marks from the casework. For finger marks / grease, use a soft, clean lint free cloth, lightly moistened with a solution of warm water and mild detergent. Do not use any alcohol or solvent based cleaning products, as they may damage the finish of the amplifiers.

**ENSURE THAT THE AMPLIFIER IS SWITCHED OFF AND DISCONNECTED FROM THE MAINS ELECTRICITY SUPPLY BEFORE UNDERTAKING ANY CLEANING.**

**Valve Life** The valves supplied with your amplifier should provide approximately 6000 hours of operation. They are specially selected by us, and should only be replaced with matched pairs. Please consult your Audio Note (UK) dealer should your valves need replacing.

## TECHNICAL SPECIFICATIONS

<b>INPUT IMPEDANCE</b>	600 Ohm, line level
<b>INPUT SENSITIVITY</b>	1.4V for full output
<b>MAXIMUM OUTPUT</b>	20 watts (approximate) per channel into 4 or 8 Ohm loads
<b>CHANNEL BALANCE</b>	+/- 0.3dB
<b>VALVE COMPLEMENT</b>	2 x 5R4WGB 2 x GE VT4-C 2 x 6V6
<b>UNIT WEIGHT</b>	48KG
<b>SHIPPING WEIGHT (ORIGINAL PACKAGING)</b>	58.5KG
<b>UNIT DIMENSIONS</b>	305mm (h) x 305mm (w) x 640mm (d)
<b>SHIPPING DIMENSIONS (ORIGINAL PACKAGING)</b>	420mm (h) x 420mm (w) x 760mm (d)
<b>MAINS INPUT</b>	AC 100-120V/220-240V 50/60 Hz
<b>MAINS FUSE</b>	3.15A Anti Surge (110/120V Supply) 1.2A Anti Surge (200/240V Supply)
<b>MAX. POWER CONSUMPTION</b>	200 Watts
<b>NOTE</b>	Due to Audio Note (UK)'s ongoing research and development program, specifications are subject to change without notice.

# WARRANTY INFORMATION

Audio Note (UK) warrants this product to be free from defects in materials and workmanship for two years from the original date of purchase from an appointed Audio Note (UK) dealer, and agrees to cover the cost of parts and associated labour required to correct such defects, subject to terms & conditions.

This Warranty is offered to the first purchaser only.

Any valves supplied with the unit are warranted for three months from the original date of purchase.

If the product fails in normal domestic use and during the Warranty period due to the above described faults or defects, Audio Note (UK) will, at its discretion, repair or replace the item free of charge within a reasonable time once it has been returned to Audio Note (UK) or an appointed Audio Note (UK) dealer or service engineer.

Audio Note (UK) is not liable for any shipping charges incurred whilst transporting the product to or from Audio Note (UK) or an appointed Audio Note (UK) dealer or service engineer, should the item require service or repair during or after the Warranty period.

If the product must be shipped, please use the original packaging materials and include a copy of the original sales receipt along with a note explaining, in as much detail as possible, the problems you are experiencing with the unit.

**Only use a reputable Courier Service or Shipping Agent, and ensure that your product is insured during transit.**

**Any servicing, repairs or modifications not authorized by Audio Note (UK), or carried out by persons other than appointed Audio Note (UK) service engineers will invalidate any warranty.**

This Warranty does NOT cover: -

Damage sustained whilst in the possession of a shipping agent, retailer or consumer and not caused as a direct result of defects in materials or workmanship.

Damage caused by normal wear and tear.

Damage or defects caused by abnormal or unreasonable use.

Damage caused by accident, acts of nature, misuse or neglect.

Damage caused by a failure to follow the operating and installation instructions supplied with the product.

Damage caused by improper or careless cleaning.

Audio Note (UK) reserves the right to refuse warranty for any component of which the serial number has been removed, defaced or tampered with.

## CONTACT INFORMATION

If in the future your Audio Note (UK) product requires servicing, or if you require technical support or have any questions regarding this or any of our other products, please contact your local Audio Note (UK) dealer.

Alternatively, please feel free to contact us directly: -

Audio Note (UK) Limited  
Viscount House  
Star Road, Star Trading Estate  
Partridge Green  
West Sussex  
RH13 8RA  
United Kingdom

Tel: +44 (0)1273 830 800  
Fax: +44 (0)1273 731 498  
e-mail: [info@audionote.co.uk](mailto:info@audionote.co.uk)

